



DS-16G-ER-Dxxx

SFP+, 16/8/4G FC, DWDM 100GHz grid, 192.00 - 196.00THz (41ch), 40km, 13dB, LC, D2955-D6142

OVERVIEW

The DS-16G-ER-Dxxx is a versatile DWDM transceiver in SFP+ form-factor supporting a wide range of Fiber Channel (FC) services (4G to 16G). The transceiver has been layer-1 tested and approved by Cisco.

For diagnostic purposes, the transceiver supports optical (OWRAP) and electrical (EWRAP) loop-back functionality, with or without forwarding. The transceiver is provided in 41 channel versions at the 100GHz DWDM grid as specified in the ITU-T 694.1 standard. The transceiver can also be used in 1550/1530nm CWDM applications by selecting wavelength versions that match these.

The optical performance provides a bridgeable distance of up to 40km (without dispersion compensation) for 16G FC. This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

The transceiver module is compliant to RoHS-6/6.

TECHNICAL DATA

Parameter	Value
Technology	DWDM 100GHz SFP+
Transmission media	SM (2x LC)
Typical reach	40km
Nominal wavelengths	192.00 - 196.00THz (41ch)
Bit rate support	14.025Gbps 8.500Gbps 4.250Gbps
Protocol support	16G FC 8G FC 4G FC
Power budget	6 – 13dB @ 16G FC 6 – 14dB @ 8G/4G FC
Dispersion tolerance	800ps/nm ¹⁾
Dispersion penalty	Max 2dB
Power consumption	< 2.2W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

¹⁾ Average power


²⁾ @ BER < 1E-12 using PRBS 2³¹-1

Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

Parameter	Value
Transmitter data:	
Output power	Min: 0.0dBm ¹⁾ Max: +4.0dBm ¹⁾
Transmit wavelengths	192.00 - 196.00THz 100GHz (ITU-T G.694.1)
Receiver data:	
Minimum input power 16G FC	-13.0dBm ^{1) 2)}
8G FC	-14.0dBm ^{1) 2)}
4G FC	-14.0dBm ^{1) 2)}
Overload (max power)	-2.0dBm ^{1) 2)}
Wavelength range	1480 - 1580nm
DDM	Yes
MSA compliance	SFF-8431, -8432, -8472



OWRAP with forwarding

EWRAP with forwarding

Subject to change without notice.

For more information visit smartoptics.com.

smartoptics

ORDERING INFORMATION

Ordering number	Frequency THz	Wavelength nm	Ordering number	Frequency THz	Wavelength nm
DS-16G-ER-D6142	192.00	1561.42	DS-16G-ER-D4453	194.10	1544.53
DS-16G-ER-D6061	192.10	1560.61	DS-16G-ER-D4373	194.20	1543.73
DS-16G-ER-D5979	192.20	1559.79	DS-16G-ER-D4294	194.30	1542.94
DS-16G-ER-D5898	192.30	1558.98	DS-16G-ER-D4214	194.40	1542.14
DS-16G-ER-D5817	192.40	1558.17	DS-16G-ER-D4135	194.50	1541.35
DS-16G-ER-D5736	192.50	1557.36	DS-16G-ER-D4056	194.60	1540.56
DS-16G-ER-D5655	192.60	1556.55	DS-16G-ER-D3977	194.70	1539.77
DS-16G-ER-D5575	192.70	1555.75	DS-16G-ER-D3898	194.80	1538.98
DS-16G-ER-D5494	192.80	1554.94	DS-16G-ER-D3819	194.90	1538.19
DS-16G-ER-D5413	192.90	1554.13	DS-16G-ER-D3740	195.00	1537.40
DS-16G-ER-D5333	193.00	1553.33	DS-16G-ER-D3661	195.10	1536.61
DS-16G-ER-D5252	193.10	1552.52	DS-16G-ER-D3582	195.20	1535.82
DS-16G-ER-D5172	193.20	1551.72	DS-16G-ER-D3504	195.30	1535.04
DS-16G-ER-D5092	193.30	1550.92	DS-16G-ER-D3425	195.40	1534.25
DS-16G-ER-D5012	193.40	1550.12	DS-16G-ER-D3347	195.50	1533.47
DS-16G-ER-D4932	193.50	1549.32	DS-16G-ER-D3268	195.60	1532.68
DS-16G-ER-D4851	193.60	1548.51	DS-16G-ER-D3190	195.70	1531.90
DS-16G-ER-D4772	193.70	1547.72	DS-16G-ER-D3112	195.80	1531.12
DS-16G-ER-D4692	193.80	1546.92	DS-16G-ER-D3033	195.90	1530.33
DS-16G-ER-D6142	193.90	1546.12	DS-16G-ER-D2955	196.00	1529.55
DS-16G-ER-D4532	194.00	1545.32			

GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally 1E ⁻¹² . Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally 1E ⁻¹² .
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.

Subject to change without notice.

For more information visit smartoptics.com.

smartoptics