

SO-SFP-155M-L80D-Cxx

SFP, 100 - 155Mbps, CWDM, DDM, 29dB, 80 km, 1270nm-1610nm (18ch)

OVERVIEW

The SO-SFP-155M-L80D-Cxx is a CWDM transceiver for 155 Mbps SDH/SONET and Fast Ethernet services (100M). The optical performance provides a bridgeable distance of up to 80 km.

The transceiver is available in 18 CWDM wavelengths, spanning from 1270nm to 1610nm in accordance with the G.694.2 standard. This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

TECHNICAL DATA

Parameter	Value
Technology	CWDM SFP
Transmission media	SM (2x LC)
Typical reach	80km
Nominal wavelength	1270 – 1610nm (18ch)
Bit rate support	100 to 155Mbps
Protocol support	FE, STM1/OC3
Power budget	8 – 29dB
Dispersion tolerance	1600ps/nm
Dispersion penalty	Max 1dB
Power consumption	< 1.0W
Operating temperature	-0°C to +70°C
Storage temperature	-40°C to +85°C

Parameter	Value
Transmitter data:	
Output power	Min: -5.0dB ¹⁾ Max: 0dBm ¹⁾
Transmit wavelength	1271nm – 1611nm G.694.2
Receiver data:	
Minimum input power	-34dBm ^{1) 2)}
Overload (max power)	-8dBm ¹⁾
Wavelength range	1100nm – 1650nm
LOS Assert	Min -45dBm
LOS De-assert	Max -35dBm
Hysteresis	Min 0.5dB
DDM	Yes
MSA compliance	SFF-8431, -8432, -8472

¹⁾ Average power.

²⁾ @ 155Mbps, BER 1×10^{-10} , PRBS $2^{31}-1$.

Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

ORDERING INFORMATION

Ordering code	Description
SO-SFP-155M-L80D-C27	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1270nm
SO-SFP-155M-L80D-C29	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1290nm
SO-SFP-155M-L80D-C31	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1310nm
SO-SFP-155M-L80D-C33	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1330nm
SO-SFP-155M-L80D-C35	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1350nm
SO-SFP-155M-L80D-C37	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1370nm
SO-SFP-155M-L80D-C39	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1390nm
SO-SFP-155M-L80D-C41	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1410nm
SO-SFP-155M-L80D-C43	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1430nm
SO-SFP-155M-L80D-C45	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1450nm
SO-SFP-155M-L80D-C47	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1470nm
SO-SFP-155M-L80D-C49	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1490nm
SO-SFP-155M-L80D-C51	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1510nm
SO-SFP-155M-L80D-C53	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1530nm
SO-SFP-155M-L80D-C55	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1550nm
SO-SFP-155M-L80D-C57	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1570nm
SO-SFP-155M-L80D-C59	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1590nm
SO-SFP-155M-L80D-C61	SFP, STM-1/OC3, 100M Ethernet, CWDM, 80km, 29dB, LC, 1610nm

GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally $1E^{-12}$. Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally $1E^{-12}$.
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.