

SO-SFP-L160DH-Cxx & -Cxx-E

SFP, 1.0625/1.25Gbps, CWDM, DDM, 41dB, 160km, 1270 – 1610nm (18ch)

OVERVIEW

The SO-SFP-L160DH-Cxx is a high power CWDM transceiver for Gigabit Ethernet (GbE) and 1G Fiber channel (1G FC). The optical performance provides a bridgeable distance of up to 160km.

The transceiver is available in 18 CWDM wavelength versions, spanning from 1270nm to 1610nm in accordance with the G.694.2 standard. This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

The transceiver is available in two temperature range options, one being an extended range: -20°C to 85°C (-4°F to 185°F).

TECHNICAL DATA

Parameter	Value
Technology	CWDM SFP
Transmission media	SM (2x LC)
Typical reach	160km
Nominal wavelength	1270 – 1610nm (18ch)
Bit rate support	1.0625/1.25Gbps
Protocol support	GbE 1G FC
Power budget	17 – 41dB
Dispersion penalty	Max 1dB
Power consumption	< 1W
Operating temperature	-0°C to +70°C -20°C to +85°C (-E)
Storage temperature	-40°C to +85°C

Parameter	Value
Transmitter data:	
Output power	Min: +4.0dBm ¹⁾ Max: +7.0dBm ¹⁾
Transmit wavelength	1271 to 1611nm (G.694.2)
Receiver data:	
Minimum input power	-37.0dBm ^{1) 2)}
Overload (max power)	-10.0dBm ^{1) 2)}
Wavelength range	1260nm – 1620nm
LOS Assert	Min -50dBm
LOS De-assert	Max -38dBm
LOS Hysteresis	Min 0.5dB
DDM	Yes
MSA compliance	SFF-8431, -8432, -8472

¹⁾ Average power

²⁾ @ 1.25Gbps, BER 1x10⁻¹², PRBS 2⁷-1, back-to-back.

Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

ORDERING INFORMATION

Ordering code	Description	Ordering code	Description
SO-SFP-L160DH-C27	SFP 1GE FC CWDM 160km HP 1270nm	SO-SFP-L160DH-C27-E	SFP 1GE FC CWDM 160km HP 1270nm-E
SO-SFP-L160DH-C29	SFP 1GE FC CWDM 160km HP 1290nm	SO-SFP-L160DH-C29-E	SFP 1GE FC CWDM 160km HP 1290nm-E
SO-SFP-L160DH-C31	SFP 1GE FC CWDM 160km HP 1310nm	SO-SFP-L160DH-C31-E	SFP 1GE FC CWDM 160km HP 1310nm-E
SO-SFP-L160DH-C33	SFP 1GE FC CWDM 160km HP 1330nm	SO-SFP-L160DH-C33-E	SFP 1GE FC CWDM 160km HP 1330nm-E
SO-SFP-L160DH-C35	SFP 1GE FC CWDM 160km HP 1350nm	SO-SFP-L160DH-C35-E	SFP 1GE FC CWDM 160km HP 1350nm-E
SO-SFP-L160DH-C37	SFP 1GE FC CWDM 160km HP 1370nm	SO-SFP-L160DH-C37-E	SFP 1GE FC CWDM 160km HP 1370nm-E
SO-SFP-L160DH-C39	SFP 1GE FC CWDM 160km HP 1390nm	SO-SFP-L160DH-C39-E	SFP 1GE FC CWDM 160km HP 1390nm-E
SO-SFP-L160DH-C41	SFP 1GE FC CWDM 160km HP 1410nm	SO-SFP-L160DH-C41-E	SFP 1GE FC CWDM 160km HP 1410nm-E
SO-SFP-L160DH-C43	SFP 1GE FC CWDM 160km HP 1430nm	SO-SFP-L160DH-C43-E	SFP 1GE FC CWDM 160km HP 1430nm-E
SO-SFP-L160DH-C45	SFP 1GE FC CWDM 160km HP 1450nm	SO-SFP-L160DH-C45-E	SFP 1GE FC CWDM 160km HP 1450nm-E
SO-SFP-L160DH-C47	SFP 1GE FC CWDM 160km HP 1470nm	SO-SFP-L160DH-C47-E	SFP 1GE FC CWDM 160km HP 1470nm-E
SO-SFP-L160DH-C49	SFP 1GE FC CWDM 160km HP 1490nm	SO-SFP-L160DH-C49-E	SFP 1GE FC CWDM 160km HP 1490nm-E
SO-SFP-L160DH-C51	SFP 1GE FC CWDM 160km HP 1510nm	SO-SFP-L160DH-C51-E	SFP 1GE FC CWDM 160km HP 1510nm-E
SO-SFP-L160DH-C53	SFP 1GE FC CWDM 160km HP 1530nm	SO-SFP-L160DH-C53-E	SFP 1GE FC CWDM 160km HP 1530nm-E
SO-SFP-L160DH-C55	SFP 1GE FC CWDM 160km HP 1550nm	SO-SFP-L160DH-C55-E	SFP 1GE FC CWDM 160km HP 1550nm-E
SO-SFP-L160DH-C57	SFP 1GE FC CWDM 160km HP 1570nm	SO-SFP-L160DH-C57-E	SFP 1GE FC CWDM 160km HP 1570nm-E
SO-SFP-L160DH-C59	SFP 1GE FC CWDM 160km HP 1590nm	SO-SFP-L160DH-C59-E	SFP 1GE FC CWDM 160km HP 1590nm-E
SO-SFP-L160DH-C61	SFP 1GE FC CWDM 160km HP 1610nm	SO-SFP-L160DH-C61-E	SFP 1GE FC CWDM 160km HP 1610nm-E

GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally 1E ⁻¹² . Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally 1E ⁻¹² .
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.