

SO-XFP-10GE-BX60D-2733/-3327

XFP, BiDi, 10G Multirate, 1270/1330nm, DDM, 21dB, 60km

OVERVIEW

The SO-XFP-10GE-BX60D is a bi-directional transceiver solution operating directly on a single-fiber without the need for a separate optical filter. This is achieved by having two transceivers that inject different wavelengths into the same single-fiber. The solution thus consists of two transceivers; SO-XFP-10GE-BX60D-2733 and SO-XFP-10GE-BX60D-3327, operating at 1270nm and 1330nm respectively. Using a single-fiber solution provides a cost-efficient solution for interconnect and it simplifies the patching since no separate transmit/receive direction has to be taken into account.

The optical performance of the transceiver pair exceeds the IEEE 802.3ae standard, providing a bridgeable distance of up to 60km for 10GbE-LAN (10GBASE-ER) and 10GbE-WAN (10GBASE-EW) services.

This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the INF-8077i specification.

TECHNICAL DATA

Parameter	Value
Technology	BiDi XFP
Transmission media	SM (1x LC)
Typical reach	60km
Nominal wavelength Tx/Rx	1270nm/1330nm & 1330nm/1270nm
Bit rate support	9.95Gbps to 11.3Gbps
Interface standards	10GBASE-ER, 10GBASE-EW
Protocol support	10GbE-LAN, 10GbE-WAN
	OTU2, OTU2e
	STM-64/OC192
Power budget	11 – 21dB
Power consumption	< 2W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

Parameter	Value
Transmitter data:	
Output power	Min: +1.0dBm ³⁾ Max: +5.0dBm ³⁾
Transmit wavelength	1260 – 1280nm ¹⁾ 1320 – 1340nm ²⁾
Receiver data:	
Minimum input power	-20.0dBm ^{3) 4)}
Overload (max power)	-6.0dBm ^{3) 4)}
Wavelength range	1320 – 1340nm ¹⁾ 1260 – 1280nm ²⁾
LOS assert	Min -34dBm
LOS de-assert	Max -22dBm
DDM	Yes
MSA compliance	INF-8077i, XFP MSA

¹⁾ SO-XFP-10GE-BX60D-2733.

²⁾ SO-XFP-10GE-BX60D-3327.

³⁾ Average power.

⁴⁾ @ 10.3Gbps, BER ≤ 1x10⁻¹², PRBS 2³¹-1, back-to-back.

Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

Note: IEEE 802.3ae 10GBASE-ER/EW is defined only at 1550nm. The standard is referred to from bridgeable distance perspective.

Subject to change without notice.

For more information visit smartoptics.com.

smartoptics

ORDERING INFORMATION

Ordering code	Description
SO-XFP-10GE-BX60D-2733	XFP, BiDi, 10G Multirate 9.95-11.1Gbps, Tx/Rx=1270/1330nm, 60km, 21dB, LC
SO-XFP-10GE-BX60D-3327	XFP, BiDi, 10G Multirate 9.95-11.1Gbps, Tx/Rx=1330/1270nm, 60km, 21dB, LC

GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally $1E^{-12}$. Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally $1E^{-12}$.
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.