

QSFP28 100GE SR BiDi

QSFP28, 100G Eth, SRBD, MM, 850nm / 910nm, 100m, 2.4dB, LC

TQ2016-MS2C-SO

The TQ2016-MS2C-SO is a pluggable QSFP28 transceiver designed for high capacity 100 Gigabit Ethernet (100GbE) Data Center Interconnect (DCI) applications up to 100m over a multimode fiber.

TQ2016-MS2C-SO has an optical performance enabling distances of up to 100m over a Multi-Mode (MM) OM4 fiber-pair cable. The module includes FEC coding Forward Error Correction (KP4 FEC) to ensure reliable system operation. The host system shall thus not have FEC activated. The optical parameters will provide a bit error ratio (BER) of 2.4×10^{-4} . FEC will render in the required BER of better than 1×10^{-12} .

The transceivers provide digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

TECHNICAL DATA

| Parameter | Value |
|-----------------------|--|
| Technology | BiDi QSFP28 |
| Transmission media | MM (2x LC) |
| Typical reach | 70m @ OM3, 100m @ OM4 |
| Nominal wavelengths | $\lambda 1$: 850nm $\lambda 2$: 908nm |
| Interface standards | 100GBASE |
| Bit rate support | 106.25Gbps ¹⁾ 26.5625Gbd ²⁾ |
| Protocol support | 100GbE |
| Power budget | 0 – 2.4dB |
| Power consumption | < 4.0W |
| Operating temperature | 0°C to +70°C |
| Storage temperature | -40°C to +85°C |

¹⁾ Aggregated line rate 100GbE with FEC

²⁾ Line baud rate

³⁾ Average power, per lane.

⁴⁾ A received power below this value cannot be compliant; however, a value above this does not ensure compliance.


⁵⁾ Specified at BER 2.4×10^{-4}

Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

| Parameter | Value |
|-----------------------------|--|
| Transmitter data: | |
| Output power, per lane | Max: +4.0dBm ³⁾ Min: -6.2dBm ³⁾ |
| Output power, per lane, OMA | Max: +3.0dBm Min: -4.2dBm |
| Transmit wavelengths | 844 – 863nm 900 – 918nm |
| Receiver data: | |
| Receiver sensitivity, OMA | -6.6dBm ⁵⁾ |
| Minimum input power | -8.2dBm ^{3) 4)} |
| Overload (max power) | +4.0dBm ^{3) 5)} |
| Wavelength range | 844 – 863nm 900 – 918nm |
| LOS Assert | -30.0dBm ³⁾ |
| LOS De-assert | -5.9dBm ³⁾ |
| DDM | Yes |
| MSA compliance | QSFP28 MSA SFF-8472 |



| | | |
|-------------|-------|--------|
| $\lambda 1$ | 850nm | T1, R1 |
| $\lambda 2$ | 908nm | T2, R2 |

ORDERING INFORMATION

| Ordering number | Description |
|-----------------|----------------------------------|
| TQ2016-MS2C-SO | QSFP28 100GE-SRBD Duplex MM 100m |

GENERAL DEFINITIONS

| Parameter | Description |
|------------------------------|--|
| Technology | Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors. |
| Transmission Media | Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO). |
| Typical reach | Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties. |
| Bit rate range | Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps). |
| Protocols | Protocols within supported bit rate range. |
| Nominal wavelength | Typical wavelength(s) from transmitter. |
| Interface standards | Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc. |
| Power budget | Min and max power budget between Transmitter and Receiver w/o optical path penalties. |
| Dispersion tolerance/penalty | Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate. |
| Temperature range | Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F) |
| Power consumption | Worst case power consumption. Will vary over temperature. |
| Transmitter Output power | Average output power. Provided in min and max values. |
| Receiver minimum input power | Minimum average input power at specified BER, normally $\leq 1 \times 10^{-12}$. Some protocols require FEC to achieve sufficient BER. |
| Receiver max input power | Maximum average input power giving a BER, normally $\leq 1 \times 10^{-12}$. |
| DDM | Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA. |

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.