

# QSFP-DD 400GBASE-SR8 MPO, CMIS4.0

QSFP-DD 400GBASE-SR8, 8x50G-SR, PAM4 CMIS4.0, 8x850 nm 100m 2.0dB MPO APC

## TQD024-M85C-SO

The TQD024-M85C-SO is a QSFP-DD form-factor transceivers for 400Gbps Ethernet applications. It is intended for use in inter- and intra-connect applications within data centers between switches, routers, storage equipment etc. The optical performance is in accordance with the 400GBASE-SR8 IEEE 802.3cd standard, i.e. for optical distances up to 100m over a MultiMode (MM) OM4-grade ribbon fiber.

The electrical interface consists of eight 53.125G signals (400GAUI-8) that are converted to eight PAM4-modulated channels/lanes to transport the Ethernet signal. The transceiver can also be set in 8x50GAUI-1 mode to enable 400G to 8x 50G optical break-out configurations. Digital diagnostics functions are available via an I2C interface, as specified by the QSFP-DD MSA. The optical interface to the transceiver is an angled polished (APC) MPO16 connector.

Forward Error Correction (FEC) is required to be implemented by the host in order to ensure reliable system operation. The FEC type shall be as defined in IEEE802.3bj, i.e. Reed Solomon RS(528,514). The optical parameters will provide a bit error ratio (BER) of  $2.4 \times 10^{-4}$ .

## TECHNICAL DATA

Parameter	Value
Technology	Grey QSFP-DD
Transmission media	MM (MPO-16 APC)
Typical reach	70m @ OM3, 100m @ OM4
Nominal wavelength	8x 850nm
Interface standards	400GBASE-SR8
Electrical interfaces	400GAUI-8 or 4x100GAUI-2
Bit rate support	425Gbps <sup>1)</sup> 53.125Gbd <sup>2)</sup>
Protocol support	400GbE, 8x50GbE
Power budget	0 – 2.0dB
Power consumption	< 8W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

<sup>1)</sup> Aggregated line rate 400GbE

<sup>2)</sup> Line baud rate

<sup>3)</sup> Average receive power, (min) is informative and not the principal indicator of signal strength. A received power below this value cannot be compliant; however, a value above this does not ensure compliance.

<sup>4)</sup> Specified at BER  $2.4 \times 10^{-4}$

Parameter	Value
<b>Transmitter data:</b>	
Output power, per lane	Min: -6.5dBm <sup>3)</sup> Max: +4.0dBm
Output power, OMA outer, per lane	Min: -4.5dBm Max: +3.0dBm
ER	Min: 3dB
Transmit wavelength	840 – 860nm
<b>Receiver data:</b>	
Receiver sensitivity, OMA, per lane	-6.5dBm <sup>4)</sup>
Minimum input power, per lane	-8.5dBm <sup>3)</sup>
Overload (max power), per lane	+4.0dBm
Wavelength range	840 – 860nm
LOS Assert	Min -30dBm
LOS De-assert	Max -9dBm
LOS Hysteresis	Min 0.5dB
DDM	Yes
MSA compliance	QSFP-DD MSA CMIS4.0

### Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

Subject to change without notice.

For more information visit [smartoptics.com](http://smartoptics.com).

smartoptics

## APPLICATION CODE LIST

CMIS Application Code	Host format	Electrical interface	Payload	FEC	MSA
1	400GBASE-R	1x 400GAUI-8 (8x 50G)	400G	RS-FEC	400GBASE-SR8
2	8 x 50GBASE-R	8x 50GAUI-1 (1x 50G)	400G	RS-FEC	50GBASE-SR
3	4 x 100GBASE-R	4x 100GAUI-2 (4x 100G)	400G	P-FEC	100GBASE-SR2

## ORDERING INFORMATION

Ordering number	Description
TQD024-M85C-SO	QSFP-DD 400G SR8 100m CMIS4.0 MPO

## GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally $1E^{-12}$ . Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally $1E^{-12}$ .
Optical modulation Amplitude, OMA	Optical Modulation Amplitude is a parameter that, in certain standards, specifies the output power and receiver sensitivity. To measure the OMA, a oscilloscope with a baud rate corresponding to the transceiver is required. Thus, this parameter cannot be measured using an ordinary optical power meter.
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.

