

QSFP-DD 800G 2xFR4, CMIS5.0

QSFP-DD, 800G Ethernet, 2x400G-FR4, PAM4 CMIS5.0, 13xxnm 2km 4.2dB Dual-LC

TD8003-SC4C-SO

The TD8003-SC4C-SO is an QSFP-DD800 form-factor transceiver for 800Gbps or 2x400G Ethernet applications. It is intended for use in data center interconnect between switches, routers, storage equipment etc. for optical distances up to 2km over single-mode fiber. The optical interface consists of two duplex LC connectors, allowing aggregation of two 400G-FR4 transceivers.

The electrical interface consists of eight 106.25G signals (800GAUI-8) that are converted to eight PAM4-modulated channels/lanes to transport the optical signal over CWDM wavelengths. The transceiver can also be set in 2x400GAUI-4 mode to enable 2x 400G-FR4 break-out applications or 2x200GAUI-4 to enable 2x200G-FR4 applications. Digital diagnostics functions are available via an I²C interface, as specified by the CMIS revision 5.0.

The optical interface to the transceiver is two duplex LC connectors (UPC).

Forward Error Correction (FEC) is required to be implemented by the host in order to ensure reliable system operation. The FEC type shall be as defined in IEEE802.3bj, i.e. Reed Solomon RS(528,514). The optical parameters will provide a bit error ratio (BER) of 2.4×10^{-4} .

TECHNICAL DATA

Parameter	Value
Technology	Grey, QSFP-DD800 800G
Transmission media	SM (2x Duplex LC)
Typical reach	2km
Nominal wavelengths	1271nm 1291nm 1311nm 1331nm
Interface standards	2x400GBASE-FR4
Electrical interfaces	800GAUI-8 or 2x400GAUI-4
Bit rate support	850Gbps ¹⁾ 53.125Gbd ²⁾
Protocol support	800GbE
Power budget	0 – 4.2dB
Power consumption	< 14W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

¹⁾ Aggregated line rate 800GbE



²⁾ Line baud rate per lane

Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

Parameter	Value
Transmitter data:	
Output power, Average, per lane	Min: -3.2dBm Max: +4.4dBm
Output power, OMA, per lane	Min: -0.2dBm Max: +3.7dBm
Transmit wavelength	1264.5 – 1277.5nm 1284.5 – 1297.5nm 1304.5 – 1317.5nm 1324.5 – 1337.5nm
Receiver data:	
Minimum input power, Average, per lane	-7.4dBm
Overload, Average, per lane	+4.4dBm
Minimum input power, OMA per lane	-4.6dBm
Wavelength range	1264.5 – 1277.5nm 1284.5 – 1297.5nm 1304.5 – 1317.5nm 1324.5 – 1337.5nm
LOS Assert	Min -16dBm
LOS De-assert	Max -10dBm
LOS Hysteresis	Min 0.5dB
DDM	Yes
MSA compliance	OSFP MSA, CMIS5.0



Subject to change without notice.

For more information visit [smartoptics.com](https://www.smartoptics.com).

smartoptics

APPLICATION CODE LIST

CMIS Application Code	Host format	Electrical interface	Payload	FEC	MSA
1	2 x 400GBASE-R	2x 400GAUI-4-L C2M	2x 400G	RS-FEC	400G-FR4 MSA / 400GBASE-FR4
2	800GBASE-R	1x 800GAUI-8 L C2M	800G	RS-FEC	800G 2xFR4 (Undefined)
3	4 x 200GBASE-R	4x 200GAUI-2-L C2M	4x 200G	RS-FEC	200G-FR2* (Undefined)
4	8 x 100GBASE-R	8 x 100GAUI-1-L C2M	8x 100G	RS-FEC	100G-FR1* (Undefined)

ORDERING INFORMATION

Ordering number	Description
TD8003-SC4C-SO	QSFP-DD 800G-2xFR4 Ethernet, PAM4 CMIS5.0, 1271nm/1291nm/1311nm/1331nm 2km 4.2dB dual-LC

GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally $1E^{-12}$. Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally $1E^{-12}$.
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.

