QSFP112 400GBASE-FR4

QSFP112, 400G Eth FR4, SM 1271/1291/1311/1331nm, 2km, 4dB, LC

TQC003-SC4C-SO

The TQC003-SC4C-SO is a QSFP112 form-factor transceivers for 400Gbps Ethernet applications. The intended use is in data center interconnect between switches, routers, storage equipment etc. for optical distances up to 2km over a duplex SingleMode (SM) fiber cable.

The electrical interface consists of eight 106.25G signals (400GAUI-4) that are converted to four PAM4-modulated channels/lanes to transport the Ethernet signal. The transceiver can also be set in 4x100GAUI-1 mode to enable 400G to 4x 100G break-out configurations. Digital diagnostics functions are available via an I^2C interface, as specified by the QSFP112 MSA. The optical interface to the transceiver is an duplex LC connector.

Forward Error Correction (FEC) is required to be implemented by the host in order to ensure reliable system operation. The FEC type shall be as defined in IEEE802.3bj, i.e. Reed Solomon RS(544,514). The optical parameters will provide a bit error ratio (BER) of 2.4E x 10^{-4}.

The TQC003-SC4C-SO is compliant with Common Management Interface Specification CMIS5.2.

TECHNICAL DATA

Parameter	Value
Technology	Grey QSFP112
Transmission media	SM (2x LC)
Typical reach	2km
Nominal wavelengths	1271nm
	1291nm
	1311nm
	1331nm
Interface standards	400GBASE-FR4
Electrical interfaces	400GAUI-4 or 4x100GAUI-1
Bit rate support	425Gbps [1]
	53.125Gbd [2]
Protocol support	400GbE
Power budget	0 – 4.0dB
Power consumption	< 8.5W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

[1] Aggregated line rate 400GbE

[2] Line baud rate per lane

3) Average power, per lane

[4] Specified at BER 2.4x10^{-4}

Parameter	Value
Transmitter data:	
Output power, per lane	Min: -3.3dBm [3]
	Max: +3.5dBm [3]
Output power, OMA, per lane	Min: -0.3dBm [3]
	Max: +3.7dBm [3]
Transmit wavelength range	1264.5 – 1277.5nm
	1284.5 – 1297.5nm
	1304.5 – 1317.5nm
	1324.5 – 1337.5nm
Receiver data:	
Receiver sensitivity, OMA, per lane	-4.6dBm
Minimum input power, per lane	-7.3dBm [3] [4]
Overload (max power), per lane	+3.5dBm [3] [4]
Receiver wavelength range	1264.5 – 1277.5nm
	1284.5 – 1297.5nm
	1304.5 – 1317.5nm
	1324.5 – 1337.5nm
LOS Assert	Min -13dBm
LOS De-assert	Max -10dBm
LOS Hysteresis	Min 0.5dB
DDM	Yes

Safety/regulatory compliance:
TUV/UL/FDA (contact Smartoptics for latest certification information)
RoHS compliance

Subject to change without notice.

For more information visit smartoptics.com.

smartoptics

APPLICATION CODE LIST

CMIS Application Code	Host format	Electrical interface	Host Electrical ID	Payload	FEC	MSA	Media ID
1	400GBASE-R	1x 400GAUI-4-L (4x 100G)	0x50	400G	RS-FEC	400G-FR4/400GBASE-FR4 (Clause 151)	0x1D
2	2 x 200GBASE-R	2x 200GAUI-2 (2x 200G)	0x4E	400G	RS-FEC	200G FR4/200GBASE-FR4	0x00
3	4x 100GBASE-R	4x 100GAUI-1-L (1x 100G)	0x4C	100G	RS-FEC	100G-FR/100GBASE-FR1 (Clause 140)	0x15
4	IB NDR	IB NDR	0x32	400G	RS-FEC	400G-FR4/400GBASE-FR4 (Clause 151)	0x1D

ORDERING INFORMATION

Ordering number	Description
TQC003-SC4C-SO	QSFP112, 400G Eth FR4, SM 1271/1291/1311/1331nm, 2km, 4dB, LC

GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally $1E^{-12}$. Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally $1E^{-12}$.
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.